

MFM TECHNICAL BULLETIN #50809**PRODUCT: WindowWrap PSX-20, WindowWrap-Butyl, WindowWrap-Flex****SUBJECT: USE OF CAULKING IN WINDOW INSTALLATIONS**

MFM Building Products Corp. recommends that windows be installed in accordance with the installation instructions provided by the window manufacturer and that all applicable building codes are followed!

WindowWrap should be installed as recommended by the Application Instructions. Copies of the Application Instructions are available directly from MFM Building Products Corp. by telephoning toll-free: 1-800-882-7663.

The use of caulking underneath the window flange that is to be covered by WindowWrap is not necessary for securing the window against leaks. If properly installed, WindowWrap will effectively seal the flange to the sheathing and prevent the entry of water around the window opening.

Should caulking be used underneath the window flange, it must be cured and dry to the touch before WindowWrap is applied. Uncured caulking may interact with the WindowWrap adhesive and liquify. Do not apply WindowWrap over silicone-based caulks!

The outer top film surface of all WindowWrap tapes is compatible with most building caulks and sealants, including polyurethanes, acrylics, and silicones.

For additional information, contact MFM Technical Support: 1-800-882-7663.

**BUILDING PRODUCTS CORP.**

525 Orange Street
P.O. Box 340
Coshocton, Ohio
43812

800-882-7663
740-622-2645
fax: 740-622-6161
www.mfmbp.com