

FLEX **CLAD™ 250** DUCT & PIPE WATERPROOFING MEMBRANE

MFM Building Products Corp. manufactures a wide range of innovative waterproofing products for the building industry. With more than 55 years of field experience, MFM products are engineered for superior performance and ease of installation.

DESCRIPTION

FlexClad-250™ is a pre-fabricated self-adhering, sheet-type protective membrane. The outer layer is an embossed, UV-resistant aluminum weathering surface. Under the aluminum are multiple layers of tough, high-density cross-linked polymer film. Under the polymer film is a uniform layer of aggressive rubberized asphalt adhesive which sticks directly to metal, insulation facers and most other clean, dry surfaces. The self-adhesive surface is protected by a disposable release liner.

USES

Designed specifically to protect ductwork and sub-grade applications, FlexClad-250 can be applied over rigid board insulation, cold pipes, plenums, storage tanks, iron, copper, steel, PVC, CPVC and concrete. FlexClad can be used for piping systems, pipelines and other below grade structures. The product weatherproofs, resists water leaks and vapor transmission, preserves the efficiency of thermal insulation and reflects sunlight to reduce interior temperatures. FlexClad-250 is designed for exterior, interior or sub-grade use and it may be used in direct burial applications.

FEATURES

- All-weather, light-weight, durable and tear-resistant
- Use in place of rigid aluminum jacket or fabric/mastic systems
- Meets 25/50 Flame/Smoke Rating
- Self-stick application saves time, labor, materials, and equipment
- Seals at laps, resists moisture, protects metal and insulation
- Excellent elongation to accommodate structural movement
- Uniform thickness for optimum waterproofing performance
- Self-seals around punctures and penetrations

INSTALLATION

FlexClad-250 is a pressure sensitive product. Substrate must be properly prepared before installation. Always apply concentrated pressure to the entire surface of the membrane with a hand roller. Duct bottoms over 24" should be pinned. Please consult Installation Instructions for complete details.

LIMITATIONS

FlexClad-250 is intended to act as a weatherproofing barrier. Do not use the product as a substitute for banding, pinning or other means of securely attaching insulation and underlying materials. Follow insulation manufacturer's instructions for attaching these products. FlexClad-250 is designed to protect insulation, air handling equipment and pipelines from the infiltration of outside moisture into the system. It is not designed to handle the effects of pressure-driven moisture caused by differential temperatures, air movement or extraordinary humidity. FlexClad-250 is not designed for permanent emersion in water.

PRODUCT DATA

Installation Temperature Range	>40°F
Material Color	Aluminum, White
Roll Widths	36"
Roll Length	50 ft
Carton Weight	32 lbs
Rolls per Carton	1
Area per Carton	150 ft ²
Cartons per Pallet	30
Maximum Temp.	175°F

TECHNICAL SPECIFICATIONS

Property	Test Method	Result
Material Thickness	ASTM D 1970	25 Mils Nom.
Flexibility @ -20°F	ASTM D 1970	Pass
Vapor Permeance	ASTM E 96	.01 perms
Nail Sealability	ASTM D 1970	Pass
Heat Aging	ASTM D 794	Pass
Ultimate Elongation MD	ASTM D 412	434%
Ultimate Elongation CMD	ASTM D 412	246%

PRODUCT NUMBERS / UPC CODES

Aluminum	White
36" - 52036	36" - 52836
7 25799 52036 1	7 25799 52836 7

Slit width sizes of FlexClad-250 are available.



10-YEAR LIMITED WARRANTY
MFM Building Products Corp. (MFM) warrants materials to be free from leaks caused by defects in material or manufacturing for a period of ten (10) years from the date of purchase when applied according to published directions.

For the most current Installation Instructions, Warranties, Technical Specifications and Approvals, visit www.flexclad.com.